



**PLAN**

SCALE: 3/16" = 1'-0"

**BUILDING NOTES:**

- 1.) OPTIONAL GUTTERS WITH DOWNSPOUTS ALONG BOTH EAVES
- 2.) INSULATION: ROOF ONLY REQUIRED  
1 1/2" FIBERGLASS BLANKET WITH WHITE VINYL FACING (R-5)
- 3.) OPTIONAL 2' FIBERGLASS SKYLIGHT PANELS UNDER BOTH EAVES
- 4.) OVERHEAD DOORS: SIZE VARIES WITH EAVE HEIGHT  

EAVE HEIGHT	DOOR SIZE
10'	10' x 8'
12'	10' x 10'
14'	10' x 12'
- 5.) ALL POST TO BE PRESSURE TREATED HEM FIR NO. 1, OR: ONE SIZE LARGER USING HEM FIR NO. 2 (EXAMPLE: 6 x 6 TO 8 x 8) TREATMENT "CHEMOMITE" AT 0.60 RETENTION
- 6.) SEE DETAIL (A) FOR MAXIMUM 20d GALV. SPIKE DENSITY AT CONCRETE CAP
- 7.) 20d GALV. SPIKES TO BE EQUALLY DISTRIBUTED ON ALL 4-SIDES OF POST

NOTE: CHANGES ON THESE PLANS SHALL NOT BE ALLOWED WITHOUT WRITTEN APPROVAL BY THE ENGINEER

SYMBOL	POST SIZE	FOOTING SIZE	20d GALV. SPIKES AT CONC. CAP
A	4 x 6 RH DOOR	18" DIA. x 2'-0" DEEP	NO CONCRETE CAP REQUIRED
B	6 x 6 RH CORNER	18" DIA. x 4'-0" DEEP	36 (9 EA.SIDE)
C	6 x 8 RH END WALL	24" DIA. x 4'-0" DEEP	48 (12 EA.SIDE)
D	6 x 10 RH TRUSS SUP	36" DIA. x 4'-0" DEEP	76 (19 EA.SIDE)
E	4 x 10 RH OH DOOR SUP	24" DIA. x 4'-0" DEEP	16 (4 EA.SIDE)

JOHN C. RABY & ASSOCIATES

P.O. BOX 505 REPUBLIC WA. 99166  
509-775-2552

DO NOT SCALE DIMENSIONS FROM BLUEPRINTS