



SCALE: 1/4" = 1'-0"

BUILDING NOTES:

- 1.) OPTIONAL GUTTERS WITH DOWNSPOUTS ALONG BOTH EAVES
- 2.) INSULATION: ROOF ONLY REQUIRED
1 1/2" FIBERGLASS BLANKET WITH WHITE VINYL FACING (R-5)
- 3.) OPTIONAL 2' FIBERGLASS SKYLIGHT PANELS UNDER BOTH EAVES
- 4.) ALL POST TO BE PRESSURE TREATED HEMLOCK FIR NO. 1, OR: ONE SIZE LARGER USING HEM FIR NO. 2 (EXAMPLE: 6 x 6 TO 6 x 8) TREATMENT "CHEMONITE" AT 0.60 RETENTION
- 5.) SEE DETAIL (A) FOR MAXIMUM 20d GALV. SPIKE DENSITY AT CONCRETE CAP
- 6.) 20d GALV. SPIKES TO BE EQUALLY DISTRIBUTED ON ALL 4-SIDES OF POST

NOTE: CHANGES ON THESE PLANS SHALL NOT BE ALLOWED WITHOUT WRITTEN APPROVAL BY THE ENGINEER

SYMBOL	POST SIZE	FOOTING SIZE	20d GALV. SPIKES AT CONC. CAP
A	4 x 6 RH DOOR	16" DIA. x 2'-0" DEEP	NO CONCRETE CAP REQUIRED
B	6 x 6 RH CORNER	24" DIA. x 4'-0" DEEP	36 (9 EA.SIDE)
C	6 x 6 RH CORNER	24" DIA. x 4'-0" DEEP	36 (9 EA.SIDE)
D	6 x 6 RH END WALL	36" DIA. x 4'-0" DEEP	36 (9 EA.SIDE)
E	6 x 6 RH TRUSS SUP	48" DIA. x 4'-0" DEEP	52 (13 EA.SIDE)
F	6 x 6 RH RAFTER POST	36" DIA. x 4'-0" DEEP	44 (11 EA.SIDE)

JOHN C. RABY & ASSOCIATES

P.O. BOX 505 REPUBLIC WA. 99166
505-775-2552

DO NOT SCALE DIMENSIONS FROM BLUEPRINTS